


Type	Lamp Wattage (W)	Dimensions(mm)			Cap (B)	Lamp Current (A)	Lamp Voltage (V)	Ultraviolet Output (W)	Average Useful Life (h)	No.60901 IEC
		A Max.	B Max.	C Max.						
FPX5BLB	5	28	13	85	G23	0.180	35	0.7	4,000	0005
FPX7BLB	7	28	13	115	G23	0.180	45	1.0	4,000	0007
FPX9BLB	9	28	13	145	G23	0.180	60	1.4	4,000	0009
FPX11BLB	11	28	13	215	G23	0.155	90	1.7	4,000	0011
FPX13BLB	13	28	13	170	GX23	0.285	59	2.0	4,000	0013
FPL5BLB/K	5	28	13	85	2G7	0.180	35	0.7	4,000	2005
FPL7BLB/K	7	28	13	115	2G7	0.175	47	1.0	4,000	2007
FPL9BLB/K	9	28	13	145	2G7	0.170	60	1.4	4,000	2009
FPL11BLB/K	11	28	13	215	2G7	0.155	91	1.7	4,000	2011
FPL18BLB/K	18	40	20	225	2G11	0.375	58	3.3	4,000	2218
FPL24BLB/K	24	40	20	320	2G11	0.345	87	5.1	4,000	2224
FPL36BLB/K	36	40	20	415	2G11	0.435	87	7.2	4,000	2236
FPL55BLB/K	55	40	20	533	2G11	0.540	106	10.2	4,000	—

Dimensions

● G23 or GX23 Cap



● 2G7 or 2G11 Cap

